

FIT - 206 Fitting Package

For models:

MS 65T, MS 90T, MS 150T, MS 225T, MS 300T, MS 400T, MSSuper-1T, MSSuper-2T and MSSuper-3T
MS9 90E, MS 150E, MS 225E, MS 400E, MSSuper-1E, MSSuper-2E, MSSuper-3E

Package Contents:

- A. (1) 3/8" Brass Close Nipple
- B. (1) 3/8" Brass Close Nipple
- C. (1) 3/8"F NPT x 1/2"M NPT Brass Reducer
- D. (1) 1/2" Brass Close Nipple
- E. (3) 1/2"F NPT x 1/2"F NPT Brass Union
- F. (1) 1/2"C x 1/2"C Brass Water Supply Ball Valve
- G. (1) 3/4"F NPT x 3/4"F NPT Brass Union
- H. (3) 1/2"C x 1/2"M NPT Copper Adapter
- I. (3) 3/4"C x 3/4"M NPT Copper Adapter
- J. (1) Teflon Tape Roll

Installation:

This package contains the appropriate fittings and valves to ensure a professional plumbing installation. As each steam generator installation and corresponding plumbing runs is unique, common 1/2" (drain, steam and water) and 3/4" (pop safety) copper tubing and fittings can be purchased from a local hardware source to complete your installation. This package provides the essential, copper and brass components necessary for a serviceable and fully removeable steam generator installation.

Verify package contents (above) with IMAGE A. Locate appropriate fittings in installation IMAGE B. Install as detailed using provided teflon tape on all threaded fittings. While installing fitting package, attempt to locate unions near generator for easy access.

Note: Please refer to the steam generator manufacturer's installation and operation manual for specific and complete generator installation instructions.

*Drain Valve Supplied with Generator

