mr.steam[®]

TECHNICAL SPECIFICATIONS

AirTempo® Controls

True wireless control. A "nomadic" way to control your steam, whether installed on a wall or easily positioned on your bathroom vanity. Simply peel & stick for tool-free installation. It can even be attached to a glass shower wall.

AirTempo Control Features:

- Wall mounted, battery powered wireless control
- LCD display
- Capacitive touch panel
- 18m range from generator
- Programmable temperature
- AromaSteam Steamhead in matching finish
- RF transceiver
- Flush mount or surface mount options
- Compatibility with SteamLinxTM
- 100% waterproof electronic assembly
- Powered by two CR2450 coin cell batteries (included)

The AirTempo controls are designed to be installed inside or outside the steam room but is primarily installed inside the steam room. If the control is installed inside the steam room the control must be located:

- 1.2 1.5m above the floor
- in a location representative of the desired steam bathing temperatures. Do not locate the control above or near the steamhead or direct steam emissions.
- on a vertical wall


The communication range of the control is 18m, the wireless receiver can be moved closer to the steam room by using a longer cable if the generator is more than 18m from the steam room or if construction materials impede the wireless signal.

If the control is installed outside the steam room a Remote Temperature Probe Part Number MSTS must be installed inside the steam room.


Box Contents:

- AirTempo
- Steamhead
- Tube of Silicone Sealant
- Owner's Manual
- Wireless Receive
- Batteries
- Control Cable (1m)
- Mounting Hardware

Dimensions for the Surface Mount Control:



Dimensions for the Flush Mount Control:



FOR ILLUSTRATIVE PURPOSES ONLY. IMPORTANT NOTE: FOR SAFE AND TROUBLE FREE INSTALLATION visit mrsteam.com before installation to download the Installation, Operation and Maintenance Manual or refer to the manual provided with the unit.

MODEL	MOUNTING STYLE	FINISH	PROJECT INFORMATION
AirTempo Export	Surface Mount	PC - Polished Chrome	Location:
	Flush Mount Square* Flush Mount Round* *The flush mount kit is sold separately 104232RD or 104232SQ	BN - Brushed Nickel	Architect:
		PB - Polished Brass	Engineer:
		SB - Satin Brass	
		BB - Brushed Bronze	Contractor:
		PN - Polished Nickel	Submitted By:
		ORB - Oil Rubbed Bronze	Date:
Notes:	'		